

ACCEPTED VENDORS:
AUTOMATION DIRECT
3505 HUTCHINSON RD
CUMMING GA 30040
800-633-0405


VENDOR P/N: PSD25-0P-5800H

MANUFACTURER:
PROSENSE

TYPE: PNP
OPERATING VOLTAGE: 9.6 TO 32 VDC
OUTPUT MAX LOAD CURRENT: 500mA
CURRENT CONSUMPTION: <25mA
SET POINT: 290 TO 5800psi
SENSING MATERIAL: 316 STAINLESS STEEL
HOUSING RATING: IP67
ELECTRICAL CONNECTION: 4-PIN M12 QUICK DISCONNECT




-1 SWITCH

PSD25 Wiring Diagrams



Cable Assembly Wiring Colors:
Pin 1 - Brown
Pin 2 - White
Pin 3 - Blue
Pin 4 - Black
Note: wiring colors are based on AutomationDirect CD12L and CD12M 4-pole cable assemblies.

NOTE:
This drawing defines the overall geometry and performance specifications of the part/assembly, and constitutes the acceptance criteria thereof. Only the item(s) described in this document procured from the vendor and/or manufacturer listed hereon are approved for use. A substitute item shall not be used without prior approval. Conformance of hardware to these requirements is acceptable in lieu of vendor and/or manufacturer documentation.



—CONFIDENTIAL INFORMATION—
THE INFORMATION AND DATA CONTAINED HEREIN IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE, AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR ANY PURPOSE, WHATSOEVER, WITHOUT THE PRIOR WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.

PROTO

Paravion [®] Technology Inc.		TITLE		DRAWING NUMBER		
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: .X = ±.1 .XX = ±.05 .XXX = ±.010 ANGLES = ± 1° THREADS: INTERNAL: CLASS 2B EXTERNAL: CLASS 2A		PRESSURE SWITCH		ES50650		
		DRAWN BY	CHK'D BY	APRVD. BY	DATE	REV
		EW	LS	JT	8/17/17	A
		DO NOT SCALE DRAWING				SHEET
		3RD ANGLE PROJECTION				1 OF 1
		© 2017 PARAVION TECH. INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY INC.				